

Part- KSFSKB & KSFSKR

# Composition/ information on ingredients

Content: 80% Polyvinyl Chloride 12% Polyester 8% Carbon black Pure material name: Polyvinyl Chloride CAS No: 9002-86-2 Pure Material Name: Polyester fibre CAS No: 25038-59-9

Pure Material Name: Polyester fibre CAS No: 25038-59

Pure Material Name: Carbon black CAS No: 1333-86-4

## Hazards identification

Physical state: Thermal decomposition (above 200\_yield the following Hydro chloride irritate the respiratory tract. (Avoid inhalation of vapor and skin and eye content)

Odour: N/A

Colour: N/A

Eye Contact: Material can cause the following slight irritation.

Hazard status: N/A

Emergency Overview: N/A

#### **First Aid Measures**

Potential chronic effects:

Inhalation: Remove from exposure area to fresh air immediately. Give artificial respiration if not breathing. Get immediate medical attention.

Skin contact: Wash affected skin areas thoroughly with soap and water. Eye Contact: Flush eyes with a large amount of water for at least 15 minutes.

Ingestion: Vomiting. Rinse mouth with water. Seek medical immediately. Note to first aid, Wear class C isolating dress. Note to physician, no specific antidote. Contact poison control centre.

Fire fighting measures:

Suitable extinguishing media: Power, Co2, Foam, Water mist

Fire and Explosion hazards: N/A

Special equipment: Wear self contained breathing apparatus.

Environmental precautions: keep away from drains, water, ground and soil.

# Handling:

When using do not eat, drink or smoke. Wash hands thoroughly afterwards, avoid contact with skin and eyes. Do not breathe dust. Take precautionary measures against static discharges. Keep away from heat. Keep away form any source of ignition. Keep stored in a cool well ventilated area.

### **Physical Properties:**

Colour: Red/Blue Odour: Odourless Form: Flake Physical state: solid PH: N/A Decomposition temperature: > 200°C Auto Ignition Temperature: > 350°C Density: 1.25 ~ 1.7 Solubility: Insoluble in water Unbiodegradable Waste disposal: dispose to flame or dustin. UN classification number: UN 1361

Surface layer 107 - 109 ohms/square. Buried layer 103 - 104 ohms/square.

The information contained within this spec sheet is for guidance only. We make no warranties expressed or implied and assume no liability regarding any use of this information.(Re-view July 15)





Registered at Cardiff No. 2933918 Registered Office: Unit 4, Rivermead Drive, Rivermead Industrial Estate, Swindon, Wiltshire, SN5 7EX



#### Each kit includes:

- 1 work surface mat 600 x 600mm.
- 1 adjustable wrist-strap.
- 1 coil cord. 3.6 metres. (12ft)
- 1 straight CPG cord with croc clip. (3 metres.)
- 1 packing wallet.