



SEMBOL 100% PURE ACRYLIC ELASTOMER EXTERIOR SURFACE PAINT

DEFINITION: It is a 100% Styren acrylic copolymer emulsion based, silk matte looking exterior surface paint that can stretch up between 1 mm and 4 mm.

QUALITIES: Thanks to its flexible structure, it prevents the cracks that may occur due to shrinkage and stretching in concrete and plasters, while it provides insulation thanks to its waterproof structure. While it adheres very well to the applied surface with its superior adherence power, it also allows the surface to breathe. It is an exterior surface paint that is resistant to atmospheric conditions, pollution, sun rays, friction and impacts. It has also high coverage and washable features. This product does not harm the environment and health and does not change color over time.

APPLICATION AREA: On the outer parts of the buildings; It is used on all kinds of substrate preparation, primed, exposed concrete, smooth or rough all kinds of plastered and mineral based surfaces. Also, it can be used for decorative and protective purposes on dirty, discolored emulsion based old painted surfaces.

APPLICATION

Surface Preparation and Application: Dirt, dust and mold release agents on the surface to be newly coated should be removed by wiping, detergent or chemical washing. On glassy and shiny surfaces, a surface should be created by sanding on which the coating can hold. It definitely should not be applied to non-dry surfaces. When necessary, the raw walls are strengthened with exterior filling and repair materials, and Sembol Exterior Surface Putty is used for the repair of the capillary cracks and for stripping paste in that operation. After the surface treatment is completed, the Sembol Insulating Primer which was thinned at the rate of sixfold water is recommended for new plastered or old painted surfaces.

- **Thinner:** Water
- **Thinning Rate:** 10%
- **Form of Application:** Roller, brush
- **Drying Time:** It dries in 4-5 hours and hardens in 24 hours.
- **Coverage** : 175-225 gr/ m².
- **Recommended Primers:** Sembol Insulating Primer.
- **Application:** 6 hours after primer application to any clean, dry surface with substrate preparation, Sembol Flex Exterior Surface Paint is applied with a roller and brush.
- **Storage:** Two (2) years under proper storage conditions in unopened packaging.
- **Packaging:** 20 Kg, 10 Kg and 3.5 Kg.

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.



P410 Protect from sunlight.

P102 Keep out of the reach of children.