



SEMBOL INSULATING (TRANSPARENT) PRIMER

DEFINITION: It is an acrylic copolymer based, concentrated transparent primer that can be used both on interior and exterior surfaces.

QUALITIES: It penetrates to the surface very well and provides superior protection and saturation. Reduces paint consumption due to reducing the absorbency of the surface, prevents the surface dusting and ensures the top coat paint to adhere well to the surface.

APPLICATION AREA: It can safely be used on interior and exterior surfaces of buildings, on all kinds of unpainted and painted surfaces such as plaster, concrete, gas concrete, gypsum and plasterboard.

APPLICATION

SURFACE PREPARATION AND APPLICATION: The surface to be applied must be completely cleaned from all kinds of dirt, oil and swollen paints. In order to both saturate the surface as a primer and to ensure that the paint to be applied on surface adheres to the surface better, SEMBOL Insulating Primer is applied by brush or roller after thinning with 7 times on normal surfaces and 5 times on problematical surfaces.

- **Thinner:** Water
- **Thinning Rate:** Thinning at the ratio of 1/5 or 1/7 (in volume) depending on the surface
- **Application Type:** Roller or Brush
- **Drying Time:** Touch dry time is 3 hours, full dry time is 12 hours.
- **Coverage:** Depending on the surface, 25-40 m² / lt in a single coat
- **Packaging Options:** 15 L. 7,5 L. 2,5 L. 2,5 L. and 0,750 L.

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.