



## **SEMBOL SUPER PLASTIC PAINT**

**DEFINITION:** Styrene Acrylic copolymer based, matt interior wall paint.

**QUALITIES:** It has excellent whiteness and high coverage. It does not crack and spill, and protects the applied surface for many years without fading. It adheres very well to the surface, it is resistant to friction and wiping, also can be easily applied without leaving brush and roller marks.

**APPLICATION AREA:** It is used in the interior parts of buildings with suitable primer on all kinds of walls and ceilings, building materials such as conventional plaster, exposed concrete, chipboard, aerated concrete, brick sheetrock, gypsum plaster.

### **APPLICATION**

**Surface Preparation and Application:** The surfaces on which Sembol Super Plastic Paint will be applied must be smooth, solid, dry, clean and capable of carrying the paint. Otherwise, old, loose and swollen paint layer on the application surface should be removed from the surface. Cracked and non-smooth surfaces on the wall should be removed with satin plaster or Sembol Interior Surface Putty. The surface should be sanded and sandpaper dust should also be removed from the surface after 24 hours from the application of satin plaster or putty,. In order to prevent dusting of the surface on the plaster surfaces and increase the adherence, the surface should be primed with Sembol Insulating Primer which is thinned at a ratio of 1 to 7.

- **Thinner:** Water
- **Thinning Rate:** 10-15%
- **Drying Time:** Touch drying time is 1-2 hours. Full drying time is 24 hours.
- **Time Between Layers:** Minimum 4 hours
- **Coverage:** 12 m<sup>2</sup> / lt or 8 m<sup>2</sup> / kg in one layer depending on the surface
- **Recommended Primers:** Sembol Interior Surface Primers
- **Application:** Sembol Super Plastic Paint is thinned with water and applied on the surface in two layers by brush or roller after 6 hours from primer application.
- **Storage:** Two (2) years under proper storage conditions in unopened packaging.
- **Packaging:** 20 Kg, 10 Kg and 3.5 Kg.

### **HAZARDOUS STATEMENTS**

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

### **PRECAUTIONARY STATEMENTS :**

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.