



## **SEMBOL ACRYLIC GRAINY EXTERIOR SURFACE COATING**

**DEFINITION:** It is a styrene-acrylic emulsion based, grainy, matt looking and textural exterior surface coating material.

**QUALITIES:** By using the strong properties of the styrene-acrylic binder, it shows high resistance to surface pollution, moisture and water, and thanks to its micro-porous structure, it allows the surface it is applied to breathe. It adheres very well to the surfaces it is applied with its superior adherence power. Also, it is resistant to atmospheric conditions, sun rays, friction and impacts. It does not crack and shed in time, and its colors are not faded.

**APPLICATION AREA:** On the outer parts of the buildings; It is used on all kinds of substrate preparation, primed, exposed concrete, smooth or rough all kinds of plastered and mineral based surfaces. Also, it can be used for decorative and protective purposes on dirty, discolored emulsion based old painted surfaces.

### **APPLICATION**

**Surface Preparation and Application:** Dirt, dust and mold release agents on the surface to be newly coated should be removed by wiping, detergent or chemical washing. On glassy and shiny surfaces, a surface should be created by sanding on which the coating can hold. It definitely should not be applied to non-dry surfaces. When necessary, the raw walls are strengthened with exterior filling and repair materials, and Sembol Exterior Surface Putty is used for the repair of the capillary cracks and for stripping paste in that operation. After the sub-surface treatment is completed, 1 layer of Sembol Silicon Based Exterior Surface Primer is applied depending on the property of the surface. On old painted surfaces, Sembol Insulating Primer should be used by thinning at the rate of 1/6. After the primer application, Sembol Silicone Grainy Exterior Surface Coating is applied in a single layer with the suitable roller according to the desired pattern.

**Thinner:** Water

**Thinning Rate :** It is ready to use but it can be thinned up to 5% depending on the pattern.

**Form of Application:** Roller, coral roller

**Drying Time:** It dries in 4-5 hours and hardens in 24 hours.

**Coverage :** Depending on the desired pattern, 800-1 100 gr / m<sup>2</sup>

**Recommended Primers:** Sembol Silicon Based Exterior Surface Primer, Sembol Insulating Primer

**Application:** 6 hours after the primer application, on all kinds of clean and dry surfaces that have been already prepared for the sub-surface, the Sembol Acrylic Grainy Exterior Surface Coating is applied on the surface to be applied in an equal amount per unit area by applying a pattern with a suitable roller.

**Packaging:** 25 Kg

### **HAZARDOUS STATEMENTS**

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

### **PRECAUTIONARY STATEMENTS :**

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.