

SEMBOL UNIVERSAL PRIMER

DEFINITION: It is an acrylic emulsion based primer for filled interior and exterior walls.

QUALITIES: Thanks to its special formula, it penetrates very well to the surface it is applied on interior and exterior surfaces and provides superior protection. Since it reduces the absorbency of the surface, it decreases the paint consumption, and provides the top coat paint to adhere well to the surface.

APPLICATION AREA: It is used as primer on all interior and exterior surfaces where acrylic-based and acrylic-based silicone additive paint products will be applied, before the topcoat application.

APPLICATION: The surface to be applied must be completely cleaned from all kinds of dirt, oil and swollen paints. As a primer, it both saturates the surface and provides better adhesion of the paint to be applied on it. SEMBOL Universal Primer is applied by brush and roller after thinned with 20-25% water.

- **Thinner:** Water
- **Thinning Rate:** 20-25% thinning
- **Application Type:** Roller or Brush
- **Drying Time:** Touch dry time is 6 hours, full dry time is 12 hours.
- **Coverage:** 13 m² / lt in a single coat depending on the surface.
- **Packaging Options:** 20 Kg 10 Kg and 3,5 Kg.

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.