

SEMBOL WATER-REPELLENT (CAST STONE-NATURAL STONE) IMPREGNATION SOLUTION

DEFINITION: It is a transparent special water-repellent solution with high penetration and transparent structure. The surface also does not form a film layer.

QUALITIES: It provides excellent water repellency on absorbent exterior surfaces and mineral based surfaces. Thanks to its strong silicone structure, it provides water impermeability to the surface it is applied to. It protects the surfaces against alkalis and UV and provides resistance against negative natural factors and does not prevent the surfaces from breathing due to its porous structure.

APPLICATION AREA : It can be used safely on natural stones, clay bricks, tiles, as well as mineral-based surfaces, aerated concrete and concrete surfaces.

APPLICATION: After the looseness, dust and particles on the surfaces are cleaned, 2-3 layer should be applied as wet (without waiting to dry) on the wet surface.

THINNING: It is ready to use, it is not thinned.

DRYING TIME: 4-5 hours at 20°C and above temperatures.

COVERAGE: 3-6 m²/ Kg

STORAGE: It is one (1) years in its original unopened package under suitable storage conditions.

PACKAGING: 12 Kg, 3 Kg and 0.75 Kg

SAFETY WARNINGS:

S2 Keep out of the reach of children.

S7 / 9 Keep container tightly closed and in a well-ventilated place.

S16 Keep away from sources of ignition. - No smoking.

S23 Do not breathe vapor.

S24 / 25 Avoid contact with eyes and skin.

S29 Do not empty into drains.

S37 / 39 Wear suitable gloves, safety glasses and mask.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

RISK WARNINGS:

R10 Flammable.

R20 Harmful by inhalation.

R38 Irritating to skin.

R48 Danger of serious damage to health under prolonged exposure.

R65 Harmful: May cause lung damage if swallowed

R67 Vapors can cause drowsiness and dizziness.