



SEMBOL SEROCOAT CERAMIC LINER

DEFINITION : Acrylic dispersion based, one component, high adhesive primer applied to increase adherence and balance the absorbency of the surface before ceramic coating on vertical and glassy surfaces or ceramics.

APPLICATION AREA: It is used in horizontal and vertical applications, before ceramic coating on ceramic, to increase adherence and balance the water requirement of the cement-based plasters and screeds, solid and painted (polyurethane, epoxy and acrylic) surfaces before coating on solid vinyl tiles, wooden, parquet surfaces.

- It is ready to use and can be applied easily and quickly.
- It is water based and can be used safely indoors.
- It provides high adherence.
- It is applied before cement based coatings and prevents rapid water loss of mortar.
- It provides moisture resistance.

SURFACE PREPARATION

It should be careful about that the application surface has cured. The surface of the application should be cleaned from anti-sticking materials such as dust, oil, tar, bitumen, paint, silicone, curing agent, detergent and form oils.

APPLICATION INFORMATON

SEMBOL Seracoat Liner is ready for use. It is mixed before use and applied to the surface with a brush or roller. Apply one coat. The drying time of the product is 3 - 5 hours.

COVERAGE

300 - 500 g / m² (Varies depending on the absorbency and roughness of the application surface)

ATTENTION : Avoid applying below + 5 ° C and above + 30 ° C. Do not use in weather with a risk of freezing within 24 hours. Stir well before use. Protect it against freezing.

PACKAGE : 20 Kg 12 Kg 3 Kg and 1 Kg

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.



P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.