



SEMBOL SOFT SPECIAL MATTE SILICONE INTERIOR SURFACE PAINT

DEFINITION: It is a styrene acrylic copolymer based, special matt topcoat paint in egg shell gloss texture used for decorative and protective purposes on interior surfaces.

QUALITIES: It is a paint that has real wiping properties thanks to its special matte texture. It has high coverage, is odorless and is environmentally friendly as it is thinned with water. This product provides perfect adhesion to all kinds of surfaces. Thanks to its flexible structure, it does not crack or spill. It is easy to apply and can be used for many years without changing color.

APPLICATION AREA: It is used on all kinds of interior wall surfaces that have previously completed sub-surface preparation such as satin plaster, putty and priming.

APPLICATION

Surface Preparation and Application: After the dirt and dust on the surfaces to be painted are removed from the surface by mechanical ways, the swollen and loose, old paints on the old painted surfaces are cleaned. The cracks and level differences in the wall must be removed with satin plaster or Sembol Interior Surface Putty in order to provide the best satin texture. The surface should be sanded and sandpaper dust should be wiped away from the surface after 24 hours from the application of satin plaster or putty. Sembol Insulating Primer which is thinned at the rate of 1/7 should be used on old painted and satin plaster surfaces, and Sembol Silicone Interior Surface Primer should be used on normal surfaces. Sembol Transformation Primer should be used for transition from solvent-based old painted semi-matt surfaces to water-based surfaces.

Thinner: Water

Thinning Rate: 10%

Form of Application: Roller, brush

Drying Time: Touch drying time is 1-2 hours. Full drying time is 24 hours.

Time Between Layers: Minimum 4 hours

Coverage: 11-13 m² / lt in one layer depending on the surface

Recommended Primers: Sembol Silicon Based Interior Surface Primers

Application: Paint that has been thinned and homogenized is applied in 2 layers by roller or brush on any dry surface that has been prepared for the substrate.

Storage: Two (2) years under proper storage conditions in unopened packaging.

Packaging: 15L, 7.5L and 2.5 L

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.