

SEMBOL SUPER CEILING PAINT

DEFINITION: Acrylic copolymer based, matt, decorative and protective interior ceiling paint.

QUALITIES: It has excellent whiteness and high coverage. It does not crack and spill, and protects the applied surface for many years without fading. It is resistant to friction and wiping, also can be easily applied without leaving brush and roller marks especially on gypsum-based surfaces.

APPLICATION AREA: It is used on the ceilings of the interior surface of the buildings.

APPLICATION

Surface Preparation and Application: If the surface to be treated is new, the surface should be free from dust. In order to obtain a smoother surface, the surface is smoothened with the Sembol Interior Surface Putty. If the surface is painted, swollen and loose old paints should be removed and the entire surface should be cleaned with sandpaper. On the surfaces with satin plaster and which are suitable for dusting, Sembol Insulating Primer thinned at the ratio of 1 to 7 should be applied.

- **Thinner:** Water
- **Thinning Rate:** 20-25%
- **Drying Time:** Touch drying time is 1-2 hours. Full drying time is 24 hours.
- **Time Between Layers:** Minimum 4 hours
- **Coverage:** 7-8 m² / kg in one layer depending on the surface
- **Recommended Primers:** There is no need for primer except for satin plastered surfaces
- **Application:** Sembol Super Ceiling Paint which is thinned as described above is applied in 2 layers to clean and dry surfaces whose substrate processes are completed. Wait at least two hours between application layers.
- **Storage:** Two (2) years under proper storage conditions in unopened packaging.
- **Packaging:** 20 Kg, 17.5 Kg, 10 Kg and 3.5 Kg

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.