



SEMBOL SILICONE PLASTIC PAINT

DEFINITION: Styrene acrylic copolymer based, silicone modified, economical, matt looking interior surface paint.

QUALITIES: It adheres well to the surface, does not crack, shed, and is easy to release. It's colors do not fade, it protects the applied surface for many years.

APPLICATION AREA: It is used as topcoat interior surface paint on surfaces such as plaster, concrete and exposed concrete.

APPLICATION

Surface Preparation and Application: After the surfaces to be applied Sembol Silicone Plastic Paint are cleaned from all kinds of oil, dirt, loose and blistered layers, the surface should be smoothen and cracks should be filled with Sembol Interior Surface Paste when necessary. On the surfaces that are at risk of dusting, the Sembol Insulating Primer should be used by thinning at the rate of 1/7.

Thinner: Water

Thinning Rate: 20-25 %

Drying Time: It dries in 1-2 hours and hardens in 24 hours.

Time Between Layers: Minimum 2 hours

Coverage : 10 m² / lt or 8 m²/kg in one layer depending on the surface

Recommended Primers: Sembol Interior Surface Primers

Application: 6 hours after primer application, Sembol Silicone Plastic Paint is thinned with water and applied on the surface in two layer by brush or roller.

Storage: Two (2) years under proper storage conditions in unopened packaging.

Packaging: 20 Kg, 10 Kg and 3.5 Kg

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.