

SEMBOL SYNTHETIC THINNER

Definition: It is a mineral turpentine thinner.

Qualities: It is used as a thinner to bring all synthetic based paints, primers and varnishes to the proper use consistency. Thanks to its high volatility, it provides fast drying and making smooth film layers of the products after application.

Application: It is used to thin all synthetic products and to clean the application tools. There must be no flame and high heat materials in the application area and adequate ventilation should be provided.

Storage: Store in sealed packages, in a well-ventilated place and in a cool place.

Specifications: Density (g/cm³ at 20°C): 0.775-0.777

Item No: 04.474

Packaging: 10 L(7.8 Kg) - 3/1 L(1.50 Kg) – 2/1 L(1 Kg.) – 1/1 L(0.400 Kg.) – ½ L(0.200 Kg.)

All hazard statements:

H225 Easily flammable liquid and vapor.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if inhaled and swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful by inhalation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of causing damage to the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.