

SEMBOL WATER BASED VARNISHED WOOD PROTECTOR

DEFINITION: Sembol Water Based Varnished Wood Protector is an acrylic based glossy product formulated for use on all types of old and new wooden surfaces on exterior facades and special patterned EPS-XPS Polystyrene sheets.

APPLICATION AREA: It can be safely applied on EPS-XPS Polystyrene sheets and exterior wooden surfaces such as doors, window frames, pergolas that are above ground level and exposed to atmospheric conditions.

APPLICATION: Surfaces to be painted must be free of dirt, oil, sanding dust and old paint and varnish residues. It should be applied with brush or roller in at least 2 layers, and a 6 hour time interval should be given between the layers.

THINNING: It should be thinned with 5-10% water optionally.

DRYING TIME: Full drying time is 3-4 hours.

COVERAGE: 8-10 m² area can be painted in one layer with 1 liter product,.

STORAGE: One (1) year in its original unopened packaging under suitable storage conditions.

PACKAGING: 15 L, 7.5 L and 2.5 L

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.