



## **SEMBOL SATIN PLASTER PRIMER**

**DEFINITION:** It is a ready-to-use acrylic copolymer emulsion based transparent interior surface primer.

### **APPLICATION AREA:**

It is used for the first paint of the absorbent and dust-like surfaces to be painted for the first time, such as satin gypsum, drywall and old painted interior surfaces that have previously been painted with water or solvent-based paint which were lost its color or contaminated. And also in any kind of water based painting for decorative purposes it can be used as primer.

### **APPLICATION**

The surface must be clean and dry. Surface preparation should be done with the filling system of the blistered and poured places. Priming is done after the dust on the surface is cleaned. It is applied to the surface as a single coat with a brush, roller or spray system. The air temperature should be at least + 5°C during the application.

### **THINNING**

Apply without any thinning

### **DRY TIME (20°C)**

24 hours before topcoat paint application.

### **APPLICATION CAPACITY (As Square)**

Depending on the application and the floor, 12 to 14 m<sup>2</sup> of area can be primed with 1 L primer.

**PACKAGE :** 15 L, 7.5 L, 2.5 L, 2.5 L and 0.750 L

### **HAZARDOUS STATEMENTS**

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

### **PRECAUTIONARY STATEMENTS :**

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children

