



SEMBOL MAKROSİL SILICONE MATTE INTERIOR SURFACE PAINT

DEFINITION: It is a water based, styrene acrylic emulsion essential, silicone added, wipe resistant, matt textured and decorative top coat interior surface paint.

QUALITIES: It shows perfect adhesion to all kinds of surfaces. Thanks to its flexible structure, it does not crack or spill. It has excellent whiteness and covering, high water repellency, friction and washing resistance. This product has a special matte texture and high coverage. Also it is odorless and an environmentally friendly paint as it is thinned with water. It is easy to apply and can be used for many years without changing color.

APPLICATION AREA: It can be applied as a top coat paint on mineral surfaces that sub-ground prepared with such as satin plaster, putty and primer, on new and smooth interior walls and ceilings and on old painted interior surfaces that have discolored.

APPLICATION

Surface Preparation and Application: After the dirt and dust on the surfaces to be painted are removed from the surface by mechanical ways, the swollen and loose, old paints on the old painted surfaces are cleaned. The cracks and level differences in the wall must be removed with satin plaster or Sembol Interior Surface Putty in order to provide the best satin texture. The surface should be sanded and sandpaper dust should be wiped away from the surface after 24 hours from the application of satin plaster or putty. Sembol Insulating Primer which is thinned at the rate of 1/7 should be used on old painted and satin plaster surfaces, and Sembol Silicone Interior Surface Primer should be used on normal surfaces.

Thinner: Water

Thinning Rate: Should be thinned at the rate of 15-20%

Form of Application: Roller, brush

Drying Time: Touch drying time is 1-2 hours. Full drying time is 24 hours.

Time Between Layers: Minimum 4 hours

Coverage: 10-12 m² / lt in one layer depending on the surface

Recommended Primers: Sembol Insulating Primer Astar, Sembol Silicon Based Interior Surface Primer

Application: Paint that has been thinned and homogenized is applied in 2 layers by roller or brush on any dry surface that has been prepared for the substrate.

Storage: Two (2) years under proper storage conditions in unopened packaging.

Packaging: 20 Kg, 10 Kg, and 3.5 Kg

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.