

SEMBOL TRANSFORMATION PRIMER

DEFINITION: Acrylic emulsion essential, water based primer with very good adhesion and covering properties.

QUALITIES: It is a specially prepared conversion primer for painting all types of solvent-based paints with water-based paints.

APPLICATION: Old surfaces painted with solvent-based or water-based satin paint are primed with SEMBOL Transformation Primer after sanding and cleaning from dust. If necessary, two layers can be applied. After applying the primer, wait 24 hours for the painting process.

- **Thinner:** Water
- **Thinning Rate:** 20-25% thinning
- **Application Type:** Roller or Brush
- **Drying Time:** Touch dry time is 6 hours, full dry time is 12 hours.
- **Waiting Time Between Layers:** Minimum 12 hours
- **Coverage:** 13 m² / lt or 10 m² / kg in a single coat depending on the surface.
- **Packaging Options:** 20 Kg. 10 Kg. 3,5 Kg.

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.