

PROFESSIONAL SYNTHETIC ANTIRUST

DEFINITION: It is the first layer primer paint with anticorrosive feature developed for solvent based metal surfaces that are synthetic alkyd resin essential.

APPLICATION AREA : It is used as rust inhibitor in all kinds of indoor and outdoor metal parts.

APPLICATION: It can be applied with brush roller and spraying gun. The metal surface to be painted should be free from dirt, oil, dust, rust and old paint. Therefore, the surface must be thoroughly cleaned by wire brush, scraper or sandblast. Professional Synthetic Antirust should be applied in two layers, after 8-9 hours later from the application the last layer paint can be applied.

THINNING: Can be thinned 10-15% with synthetic thinner

DRYING TIME : Touching drying time is 2 hours, Dust-free drying time is 3-4 hours, Harden drying time is 8 hours.

	COVERAGE: 10-12
m ² /lt	

STORAGE: At least one
(1) year under proper storage conditions in unopened packaging.

PACKAGING: 18 Kg, 2.75 Kg.

HAZARDOUS STATEMENTS

H226 Flammable liquid and vapor.

H304 May be fatal if inhaled and swallowed.

H336 May cause drowsiness or dizziness.

H412 Long lasting, harmful effect in aquatic environment.

EUH066 May cause skin dryness and cracks in repeated exposure.

PRECAUTIONARY STATEMENTS :

P210 Keep away from heat / sparks / flames / hot surfaces. - No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapor / spray.

P302+P352 IF CONTACT WITH SKIN: Wash with plenty of soap and water.

P333 + P313 IF IRRITATION OR ITCHING IS ON THE SKIN: Get medical advice / attention.

P403 + P235 Store in a well-ventilated place. Keep it cold.

P103 Read the label before using.

P102 Keep out of the reach of children.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P273 Avoid release to the environment.