

SEMBOL EPOXY PUTTY

COVERAGE: Mix consumption for 1 mm thickness = 1,5 Kg./m²

DEFINITION : Epoxy Resin-based, two-component, general purpose putty.

QUALITIES : It is an epoxy resin based filler and surface correction paste that does not crumple, has high strength and adhesion. It is resistant to water and chemicals.

APPLICATION : There should be no dust, oil, dirt, rust and loose ground on the surface to be applied. Some paste is mixed with some hardener on the shovel type trowel with a spatula and applied to the surface with the help of a spatula and/or trowel. It also gives very good results in thick coat applications. It can be used safely to cover faults such as paint, elevation differences, large and small cracks on the surfaces.

DRYING TIME: Drying time 24 hours. Wait at least 24 hours to apply another coat. It reaches full drying and impact resistance in 4-6 days depending on the air temperature.

FORM OF APPLICATION: Spatula, putty steel, screed

PACKAGING: A+B= 2 Kg. – 8 Kg. - 20 Kg.

Safety Warnings:

S2 Keep out of the reach of children.

S7 / 9 Keep container tightly closed and in a well-ventilated place.

S16 Keep away from sources of ignition. - No smoking.

S23 Do not breathe vapor.

S24 / 25 Avoid contact with eyes and skin.

S29 Do not empty into drains.

S37 / 39 Wear suitable gloves, safety glasses and mask.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

Risk Warnings:

R10 Flammable.

R20 Harmful by inhalation.

R38 Irritating to skin.

R48 Danger of serious damage to health under prolonged exposure.

R65 Harmful: May cause lung damage if swallowed

R67 Vapors can cause drowsiness and dizziness.

Hazardous Warnings:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 May be fatal if inhaled.

H332 Harmful by inhalation.

H400 Very toxic in the aquatic environment.

H410 Long lasting, very toxic effect in the aquatic environment.

H411 Long lasting, toxic effect in the aquatic environment.

H412 Long lasting, harmful effect in aquatic environment.

H225 Easily flammable liquid and vapor.

H226 Flammable liquid and vapor.

Precautionary Warnings:

P210 Keep away from heat / sparks / flames / hot surfaces. - No smoking.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P303 + P361 + P353 If in contact with skin (or hair): Immediately remove / remove all contaminated clothing. Rinse your skin with water / shower.

P308 + P313 Get medical attention / care if exposed or interacted.

P370 + P378 In case of fire: Use foam, carbon dioxide, dry powder or water for extinction.

P403 + P235 Store in a well-ventilated place. Keep it cold.

P501 Dispose of contents / container according to national regulations.