



SILICONE MODIFIED INTERIOR SURFACE PRIMER

DEFINITION : It is an acrylic emulsion based, silicone modified rammed interior surface primer.

QUALITIES: It penetrates the surface it is applied very well and provides superior protection. Since it reduces the absorbency of the surface, it decreases the paint consumption, and provides the top coat paint to adhere well to the surface.

APPLICATION AREA: It is used as a primer on all interior surfaces where all acrylic-based and silicone-added products will be applied before the topcoat application.

APPLICATION

SURFACE PREPARATION AND APPLICATION:

The surface to be applied must be completely cleaned from all kinds of dirt, oil and swollen paints. As a primer, it both saturates the surface and provides better adhesion of the paint to be applied on it. SEMBOL Silicone Modified Interior Surface Primer is applied by brush and roller after thinned with 20-25% water.

- **Thinner:** Water
- **Thinning Rate:** 20-25% thinning
- **Application Type:** Roller or Brush
- **Drying Time:** Touch dry time is 6 hours, full dry time is 12 hours.
- **Coverage:** 13 m² / lt or 10 m² / kg in a single coat depending on the surface.
- **Packaging Options:** 20 Kg, 10 Kg and 3,5 Kg

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.