



EXPOSED CONCRETE PRIMER

DEFINITION: Acrylic copolymer emulsion based, surface filler, exposed concrete primer.

APPLICATION

AREA:

It is used as a primer on exposed concrete surfaces with high water absorption, on walls and ceilings, under cement and gypsum based plaster, in order to increase adherence and working time.

APPLICATION

SEMBOL Exposed Concrete Primer application surfaces; Surface should be clean and dry, free from all kinds of dirt, oil and dust. SEMBOL exposed Concrete Primer is applied on a single layer by roller. Gypsum application is started 6 hours after the application of SEMBOL Exposed Concrete Primer. It should be paid attention that the surface and ambient temperature should be at least + 5 ° C and at most + 30 ° C during the application.

Plaster and gypsum application must be started within 7 days at the latest after the application of SEMBOL Exposed Concrete Primer.

THINNING (In Volume)

You can thin up to 20% with water.

DRY TIME (20°C)

6 hours

APPLICATION CAPACITY (As Square)

Depending on the application and the floor, 1 to 5 m² of area can be primed in 1 layer with 1 kg.

PACKAGE : 12 kg and 3 kg

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children