

SEMBOL LIQUID PLASTIC COATING

DEFINITION: It is an acrylic copolymer emulsion based, super elastic waterproofing material.

QUALITIES: Thanks to its semi-fluid property, it is a long-lasting material that can be easily applied to any type of floor, and when it dries, it creates an elastic, impermeable surface and can also be colored. It is resistant to sun rays, maintains its elasticity in hot and cold differences, and provides the opportunity to breathe for the surfaces.

APPLICATION AREA: It can be used safely wherever water and moisture impermeability is desired.

APPLICATION: The surface to be coated should be a dry and clean surface, free from all kinds of dirt, oil, dust and swollen loose tissues. After applying 40% water thinned paint as a primer, Sembol Liquid Plastic Coating should be applied without thinning in a minimum of 2 layers. Each layer should be applied in the vertical direction of the previous layer. The surfaces to be applied must have a slope so as not to allow ponding. It is necessary to protect the applied surface from UV rays, so the applied surface must be protected with any coating.

THINNING : For 1st coat (for primer purposes): 40% thinning. It is applied directly without thinning in topcoat applications.

FORM OF APPLICATION: Brush, roller or spraying

DRYING TIME : It dries in 5-6 hours and hardens in 24 hours.

WAITING TIME BETWEEN LAYERS: Minimum 12 hours

COVERAGE: Depending on the application surface, 1-1.5 kg / m²

RECOMMENDED PRIMERS: The paint, thinned with 40% water, is used as a primer.

APPLICATION: Sembol Liquid Plastic Coating is applied without thinning on the completely dried primer layer with 2 layer of roller in the vertical direction of the previous coat.

STORAGE: It is two (2) years in its unopened original packaging under suitable storage conditions.

PACKAGING : 20 Kg, 10 Kg, 3 Kg and 1 Kg.

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.

