

## **SEMBOL ALUMINIUM BRONZE PAINT**

**DEFINITION:** It is a high temperature resistant hydrocarbon resin based paint that containing metallic aluminium bronze powder.

**QUALITIES:** It is a covering, shiny, metallic looking paint that is resistant to temperatures up to 120 ° C, adheres well to primed surfaces, is very easy to apply.

**APPLICATION AREA:** It is used for protective and decorative purposes on all kinds of iron and metal surfaces, surfaces where ultraviolet rays are desired to be reflected, stove, stove pipe, metal chimney painting.

**SURFACE PREPARATION AND APPLICATION:** The surfaces are cleaned with wire brush, scraper, sand blasting and cleaning solvents so that there are no foreign materials such as old paint residue, dust, oil, rust. Paint should be applied to the cleaned surface without delay.

**THINNING:** Used without thinning.

**FORM OF APPLICATION:** Brush, roller

**DRYING TIME:** Full Drying: Maximum **24** hours

**WAITING TIME BETWEEN LAYERS:** 4 hours minimum.

**COVERAGE:** Depending on the surface, 0.125-0.150 Kg/m<sup>2</sup> in a single coat.

**PACKAGING:** 12 Kg, 2.4 Kg, 0.600 Kg, 0.300 Kg, 0.160 Kg and 0.070 Kg.

### **SAFETY WARNINGS:**

S2 Keep out of the reach of children.

S7 / 9 Keep container tightly closed and in a well-ventilated place.

S16 Keep away from sources of ignition. - No smoking.

S23 Do not breathe vapor.

S24 / 25 Avoid contact with eyes and skin.

S29 Do not empty into drains.

S37 / 39 Wear suitable gloves, safety glasses and mask.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

### **RISK WARNINGS:**

R10 Flammable.

R20 Harmful by inhalation.

R38 Irritating to skin.

R48 Danger of serious damage to health under prolonged exposure.

R65 Harmful: May cause lung damage if swallowed

R67 Vapors can cause drowsiness and dizziness.

