

SEMBOL ROAD MARK PAINT

DEFINITION: It is a chlorinated rubber modified alkyd resin based, air drying, well penetrating surface, abrasion resistant and quick drying paint.

QUALITIES: Sembol Road Mark Paint, used for marking in asphalt, road, parking etc which has high wear resistance, fast drying and durability. It adheres to the surface very well as it penetrates well to surfaces, it is easily applied, and it creates a long-lasting film on the surfaces thanks to its high mechanical resistance.

APPLICATION AREA: Sembol Road Mark Paint, which can be applied on asphalt and concrete surfaces, has been developed for marking the lines of places such as roads, airports, sidewalks, pedestrian crossings etc.

APPLICATION

Surface Preparation and Application: The surface to be applied must be absolutely dry, oil free and clean. Sembol Road Mark Paint, thinned as required, is applied on the cleaned surface with a roller or airless/airbrush spray gun.

Thinner: Road Mark Thinner and /or Cellulosic Thinner

Thinning Rate

For spraying application: It is thinned by 10-15%.

For Roller application: It is thinned by 5%.

Form of Application: It is applied with brush, roller or airless/airbrush spray gun.

Drying Time: Touch Drying time is 10-15 minutes, Full Drying time is 3.5-4 hours

Waiting time between layers: Minimum 3 hours.

Coverage: Depending on the suction of the surface 0.175-0.250 Kg/m²

Packaging: 20 Kg.- 3 Kg.

Safety Warnings:

S2 Keep out of the reach of children.

S7 / 9 Keep container tightly closed and in a well-ventilated place.

S16 Keep away from sources of ignition. - No smoking.

S23 Do not breathe vapor.

S24 / 25 Avoid contact with eyes and skin.

S29 Do not empty into drains.

S37 / 39 Wear suitable gloves, safety glasses and mask.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

Risk Warnings:

R10 Flammable.

R20 Harmful by inhalation.

R38 Irritating to skin.

R48 Danger of serious damage to health under prolonged exposure.

R65 Harmful: May cause lung damage if swallowed

R67 Vapors can cause drowsiness and dizziness.

Hazardous Warnings:

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 Causes allergic skin reactions.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 May be fatal if inhaled.
H332 Harmful by inhalation.
H400 Very toxic in the aquatic environment.
H410 Long lasting, very toxic effect in the aquatic environment.
H411 Long lasting, toxic effect in the aquatic environment.
H412 Long lasting, harmful effect in aquatic environment.
H225 Easily flammable liquid and vapor.
H226 Flammable liquid and vapor.

Precautionary Warnings:

P210 Keep away from heat / sparks / flames / hot surfaces. - No smoking.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P303 + P361 + P353 If in contact with skin (or hair): Immediately remove / remove all contaminated clothing. Rinse your skin with water / shower.
P308 + P313 Get medical attention / care if exposed or interacted.
P370 + P378 In case of fire: Use foam, carbon dioxide, dry powder or water for extinction.
P403 + P235 Store in a well-ventilated place. Keep it cold.
P501 Dispose of contents / container according to national regulations.