



PANEL DOOR PAINT

DEFINITION

It is a water-based, acrylic emulsion essential, semi-matte, protective, protective top coat paint designed for panel doors.

APPLICATION AREA:

It is used as decorative topcoat paint for new or previously painted panel doors, wooden panel doors, MDF and solid wood surfaces.

QUALITIES:

- It does not smell because it does not contain solvent and thinned with water.
- It has maximum resistance against yellowing.
- It is resistant to water and chemical cleaning materials used in homes.
- It does not harm the environment and human health.
- It provides perfect adhesion to the applied surface.
- It does not have an unpleasant smell during application.

APPLICATION

The surfaces to be applied must be dry, oil-free, clean, loose and swollen paint layers have been cleaned and surface smoothing has to be made if necessary. Paint should not definitely be applied on non-dry surfaces. Surface should be sanded slightly and the sanding dust should be completely removed from the surface. Care should be taken to ensure that the surface and ambient temperatures are between + 5°C and + 30°C during application. Brush, roller and paint blaster applications can be made. It should be thinned with 10% water. 2 layer of paint are applied in roller and brush applications. It should be waited for 4-5 hours between layers.

THINNING

It is thinned with 10% water in brush and roller applications and 15% water in paint blaster application. Stir the paint well before using it.

DRYING TIME (20°C):

Touch dry time is 30-40 minutes

Full dry time is 24 hours.

COVERAGE

10-15 m² / L in a single coat depending on the surface and application type..

STORAGE

It is two (2) years in its original unopened package under suitable storage conditions.

PACKAGING

2.50 L and 0.75 L

HAZARDOUS STATEMENTS

H315 Causes skin irritation.

H317 Causes allergic skin reactions.



H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

PRECAUTIONARY STATEMENTS :

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.