



SYMBOL (CAST STONE-NATURAL STONE) VARNISH

DEFINITION: It is a solvent-based acrylic resin essential, silicon-modified, transparent varnish.

QUALITIES: It is used directly as a protective varnish on natural stone, wooden and brick, and is applied on painted surfaces to protect the paint.

APPLICATION: It is applied with a roller or brush in two layers wet on wet. Surfaces should be protected from rain and frost for at least 6-8 hours after the last coat application. The application surfaces should be cleaned from all kinds of oil, dirt, loose, blistered texture, worn old painted surfaces.

THINNING: It is ready to use, it is not thinned.

DRYING TIME: 4-5 hours at 20°C and above temperatures.

COVERAGE: 4-7 m²/ Kg.

STORAGE: It is one (1) years in its original unopened package under suitable storage conditions.

PACKAGING: 12 Kg, 3 Kg and 0,75 Kg

SAFETY WARNINGS:

S2 Keep out of the reach of children.

S7 / 9 Keep container tightly closed and in a well-ventilated place.

S16 Keep away from sources of ignition. - No smoking.

S23 Do not breathe vapor.

S24 / 25 Avoid contact with eyes and skin.

S29 Do not empty into drains.

S37 / 39 Wear suitable gloves, safety glasses and mask.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

RISK WARNINGS:

R10 Flammable.

R20 Harmful by inhalation.

R38 Irritating to skin.

R48 Danger of serious damage to health under prolonged exposure.

R65 Harmful: May cause lung damage if swallowed

R67 Vapors can cause drowsiness and dizziness.