

## **SEMBOL ACRYLIC INTERIOR - EXTERIOR SURFACE PUTTY**

### **DEFINITION**

It is a water-based, acrylic resin essential, odorless interior and exterior wall putty.

### **QUALITIES**

Creates a smooth surface by filling the cracks in the plaster surface

It can be used instead of plaster, satin plaster and oily paste. It is easy to apply, it has the feature of inhalation. It dries fast and resistant to water and moisture.

### **APPLICATION AREA**

Interior and Exterior surfaces

### **SURFACE PREPARATION**

To strengthen the surface before applying the paste, it is recommended to apply Sembol Concentrated Acrylic Primer as a primer which was thinned with water at a rate of 1/7.

### **APPLICATION**

It is ready to use. It is applied in two layers to obtain a smooth surface. Before starting the second layer application, it should be expected to dry first layer completely. After drying, any kind of paint can be applied on it with using a suitable primer on it

### **IMPLEMENTATION PROVISIONS**

**Thinning:** It is ready to use.

**Implementation Temperature:** 5-30°C

**Coverage:** 0.80 – 2 m<sup>2</sup>/kg

### **FORM OF APPLICATION**

It is applied with putty pulling materials such as trowel and spatula.

### **PACKAGING**

25 Kg - 4 Kg

### **HAZARDOUS STATEMENTS**

H315 Causes skin irritation.

H317 Causes allergic skin reactions.

H319 Causes serious eye irritation.

H412 Long lasting, harmful effect in aquatic environment.

### **PRECAUTIONARY STATEMENTS :**

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose contents / container according to national regulations.

P410 Protect from sunlight.

P102 Keep out of the reach of children.