

SEMBOL SYNTHETIC PRIMER PAINT

DEFINITION: It is a synthetic alkyd resin essential, solvent based, matt and base coat primer paint.

APPLICATION AREA: It is used as an intermediate coat primer on all kinds of indoor and outdoor surfaces, before topcoat paint, to reduce the consumption, increase adherence and increase the protection power of the topcoat paint.

APPLICATION: It is applied by brush, roller or paint spraying gun. If the surface to be painted will be non-dirty, oil-free, dust-free, rust-free and free from old paints, it provides full contact for the paint to the surface. If there are wooden surfaces, knots should be burned and then, firstly the surface should be protected with the Sembol Wood Protector and primed with the Sembol Synthetic Primer after the protection. After 8-9 hours later from the primer application the topcoat paint can be applied.

THINNING: Can be thinned 10-15% with synthetic thinner

DRYING TIME : Touching drying time is 2 hours, Dust-free drying time is 3-4 hours, Harden drying time is 8 hours.

COVERAGE: 10-12 m²/lt

STORAGE: At least two (2) year under proper storage conditions in unopened packaging.

PACKAGING: 18 Kg, 2.75 Kg. and 1 Kg.

HAZARDOUS STATEMENTS

H226 Flammable liquid and vapor.

H304 May be fatal if inhaled and swallowed.

H336 May cause drowsiness or dizziness.

H412 Long lasting, harmful effect in aquatic environment.

EUH066 May cause skin dryness and cracks in repeated exposure.

PRECAUTIONARY STATEMENTS

P210 Keep away from heat / sparks / flames / hot surfaces. - No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapor / spray.

P302+P352 IF CONTACT WITH SKIN: Wash with plenty of soap and water.

P333 + P313 IF IRRITATION OR ITCHING IS ON THE SKIN: Get medical advice / attention.

P403 + P235 Store in a well-ventilated place. Keep it cold.

P103 Read the label before using.

P102 Keep out of the reach of children.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.