

SEMBOL KURUMPAK SOOT COVERING PRIMER

QUALITIES: It is a solvent based coating primer.

APPLICATION AREA: It is used in dirty, difficult to cover chimney discharges and sooty surfaces.

APPLICATION: At least 2 layers are applied at the intervals of 2 hours in places where the surface is pre-cleaned.

THINNING: Thinner should be added to the product only if necessary.

COVERAGE: Approximately 5-6 m² of area is painted with 1 kg product. (Single coat)

STORAGE: One (1) year under proper storage conditions in unopened packaging.

PACKAGING: 0.750 L, 0.375 L and 0.200 L.

HAZARDOUS STATEMENTS

H226 Flammable liquid and vapor.

H304 May be fatal if inhaled and swallowed.

H336 May cause drowsiness or dizziness.

H412 Long lasting, harmful effect in aquatic environment.

EUH066 May cause skin dryness and cracks in repeated exposure.

PRECAUTIONARY STATEMENTS :

P210 Keep away from heat / sparks / flames / hot surfaces. - No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapor / spray.

P302+P352 IF CONTACT WITH SKIN: Wash with plenty of soap and water.

P333 + P313 IF IRRITATION OR ITCHING IS ON THE SKIN: Get medical advice / attention.

P403 + P235 Store in a well-ventilated place. Keep it cold.

P103 Read the label before using.

P102 Keep out of the reach of children.

P280 Wear protective gloves / protective clothing and use eye protector / face protector.

P273 Avoid release to the environment.